


EL-USB-2

Temperature, humidity and dew point data logger



Part of the **EasyLog** range, the EL-USB-2 reliably measures temperature, humidity and dew point.

Features

- ✓ -31°F to +176°F and 0 to 100%RH measurement range
- ✓ Stores over 16,000 readings for both temperature and humidity
- ✓ EasyLog software available as a free download
- ✓ Logging rates between 10 seconds and 12 hours
- ✓ Immediate and delayed logging start
- ✓ User-programmable alarm thresholds for both temperature and humidity
- ✓ Status indication via red/green LEDs
- ✓ Environmental protection to *IP67 *excluding RH sensor and dependent on the front cover being replaced correctly

Typical Applications

- Museum & Heritage Monitoring
- Food and Drink



Product code: EL-USB-2

| Technical specification | |
|-----------------------------|---|
| Dimensions | 4.96 x 0.98 x 0.86 in. |
| Logging rate | User selectable between 10 seconds and 12 hours |
| Operating temperature range | -31°F to +176°F |
| Battery life | Up to 3 years (at 77°F and 1 minute logging rate, LCD on) |
| Readings | 16,382 temperature, 16,382 relative humidity |

| Dew Point specification | |
|---------------------------|--|
| Accuracy (overall error)* | 3.1°F typical (-31°F to 176°F, 40 to 100%RH) |

| Temperature specification | |
|---------------------------|--------------------------------|
| Measurement range | -31°F to +176°F |
| Internal resolution | 1.0°F |
| Accuracy (overall error)* | 1.04°F typical (41°F to 140°F) |
| Long term stability | <0.04°F / year |


*The overall error takes into account the sensor accuracy and the resolution of the data logger.

| Relative Humidity specification | |
|---------------------------------|--------------------------------|
| Measurement range | 0 to 100% RH |
| Internal resolution | 0.5% RH |
| Accuracy (overall error)* | 2.25% RH typical (20 to 80%RH) |
| Long term stability | <0.25%RH/year |

| Included in the box | |
|---------------------|------------------|
| BAT 3V6 1/2AA | Battery |
| EL-USB Wall bracket | Mounting bracket |

| Accessories | |
|---------------|---|
| BAT 3V6 1/2AA | Replacement battery |
| EL-DataPad | Handheld data logger programmer and collector |

The latest version of the control software may be downloaded free of charge.



Ultimate peace of mind **RoHS**

Version 1 - EC180100

Disclaimer: The information contained herein is believed to be reliable. Hanwell Solutions Ltd. is not responsible for any incorrect or incomplete information on this datasheet and the information or product may be changed without notice. Customers should obtain and verify the latest relevant information before placing orders for Hanwell products.

hanwell.com

Tel: +44 (0)1462 688070 | Email: sales@hanwell.com